

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.09.2022

Version number 5 (replaces version 4)


Revision: 14.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking


- 1.1 Product identifier
- Trade name: **COEPLAN 2-K Super sealant glossy transp. (B)**
- UFI: TQQ6-K0Q3-800T-WVRA
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - Identified use: intended for professional use only!
- Application of the substance / the mixture: Sealing
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: KEMPER SYSTEM LTD
Kemper House
30 Kingsland Grange
Warrington
WA1 4RW
www.kempersystem.co.uk
enquiries@kempersystem.co.uk
phone: +44 (0)1925 445532
fax: +44 (0)1925 575096
- Further information obtainable from: research & development
- 1.4 Emergency telephone number: Medical Emergency information in case of poisoning:
Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240
(advisory service in German or English language)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
 - Flam. Liq. 3 H226 Flammable liquid and vapour.
 - Acute Tox. 4 H332 Harmful if inhaled.
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
 - STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
 - The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02



GHS07
- Signal word: Warning
- Hazard-determining components of labelling: Hexamethylene diisocyanate, oligomers
hexamethylene-di-isocyanate
- Hazard statements
 - H226 Flammable liquid and vapour.
 - H332 Harmful if inhaled.
 - H317 May cause an allergic skin reaction.
 - H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
- Precautionary statements
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information: EUH204 Contains isocyanates. May produce an allergic reaction.
As from 24 August 2023 adequate training is required before industrial or professional use.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.09.2022

Version number 5 (replaces version 4)

Revision: 14.09.2022

Trade name: **COEPLAN 2-K Super sealant glossy transp. (B)**

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- Description:

Mixture: consisting of the following components.

- Dangerous components:

CAS: 28182-81-2 Reg.nr.: 01-2119970543-34	Hexamethylene diisocyanate, oligomers Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥12.5-<20%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1 Reg.nr.: 01-2119457571-37	hexamethylene-di-isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.5%

- Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information:

Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Do not leave affected persons unattended.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eye.

If symptoms persist consult doctor.

- After swallowing:

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.

- For safety reasons unsuitable extinguishing agents:

Water with full jet

- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

- 5.3 Advice for firefighters

- Protective equipment:

Do not inhale explosion gases or combustion gases.

- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes

Keep away from ignition sources.

Ensure adequate ventilation

- 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.09.2022

Version number 5 (replaces version 4)

Revision: 14.09.2022

Trade name: **COEPLAN 2-K Super sealant glossy transp. (B)**

(Contd. of page 2)

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.

- 6.4 Reference to other sections

Do not flush with water or aqueous cleansing agents
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

- Information about storage in one common storage facility:

Store away from foodstuffs.

- Further information about storage conditions:

Store in dry conditions.
Protect from frost.
Keep container tightly sealed.
Recommended storage temperature: 5-30 °C

- Storage class:

3

- 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

822-06-0 hexamethylene-di-isocyanate

WEL	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
	Sen; as -NCO

- Regulatory information

WEL: EH40/2020

- Ingredients with biological limit values:

822-06-0 hexamethylene-di-isocyanate

BMGV	1 µmol creatinine/mol
	Medium: urine
	Sampling time: At the end of the period of exposure
	Parameter: isocyanate-derived diamine

- Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Appropriate engineering controls

No further data; see item 7.

- Individual protection measures, such as personal protective equipment

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Respiratory protection:

When used properly and under normal conditions, breathing protection is not required.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2
Respiratory protection - Gas filters and combination filters according to (DIN EN 141)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.09.2022

Version number 5 (replaces version 4)

Revision: 14.09.2022

Trade name: **COEPLAN 2-K Super sealant glossy transp. (B)**

(Contd. of page 3)

- Hand protection



Protective gloves

Check protective gloves prior to each use for their proper condition.
Only use chemical-protective gloves with CE-labelling of category III.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves

Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time (min.): < 480

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.1 mm

Penetration time (min.): < 10

- Eye/face protection



Tightly sealed goggles

- Body protection:

Protective goggles and facial protection - Classification according to EN 166 protective clothing (EN 13034)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Colour:	According to product specification
- Odour:	Characteristic
- Odour threshold:	Not determined.
- Melting point/freezing point:	Undetermined.
- Boiling point or initial boiling point and boiling range	146 °C
- Flammability	Not applicable.
- Lower and upper explosion limit	
- Lower:	Not determined.
- Upper:	Not determined.
- Flash point:	47 °C
- Decomposition temperature:	Not determined.
- pH	Not determined.
- Viscosity:	
- Kinematic viscosity at 20 °C	324 mm ² /s
- Dynamic:	Not determined.
- Solubility	
- water:	Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value)	Not determined.
- Density and/or relative density	
- Density at 20 °C:	1.11 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.

- 9.2 Other information

- Appearance:	
- Form:	Fluid
- Important information on protection of health and environment, and on safety.	
- Auto-ignition temperature:	Product is not selfigniting.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.09.2022

Version number 5 (replaces version 4)

Revision: 14.09.2022

Trade name: **COEPLAN 2-K Super sealant glossy transp. (B)**

(Contd. of page 4)

<ul style="list-style-type: none"> - Explosive properties: - Solvent separation test: - VOC (EC) - Change in condition - Evaporation rate 	<p>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</p> <p>39.60 %</p> <p>Not determined.</p>
--	--

- Information with regard to physical hazard classes

<ul style="list-style-type: none"> - Explosives - Flammable gases - Aerosols - Oxidising gases - Gases under pressure - Flammable liquids - Flammable solids - Self-reactive substances and mixtures - Pyrophoric liquids - Pyrophoric solids - Self-heating substances and mixtures - Substances and mixtures, which emit flammable gases in contact with water - Oxidising liquids - Oxidising solids - Organic peroxides - Corrosive to metals - Desensitised explosives 	<p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Flammable liquid and vapour.</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p>
--	---

SECTION 10: Stability and reactivity

<ul style="list-style-type: none"> - 10.1 Reactivity - 10.2 Chemical stability - Thermal decomposition / conditions to be avoided: - 10.3 Possibility of hazardous reactions - 10.4 Conditions to avoid - 10.5 Incompatible materials: 	<p>No further relevant information available.</p> <p>No decomposition if used according to specifications. Reacts with water. Reacts with alcohols, amines, aqueous acids and alkalis. Reacts with humid air. Reacts with alcohols.</p> <p>No further relevant information available.</p> <p>No further relevant information available.</p>
--	---

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.09.2022

Version number 5 (replaces version 4)

Revision: 14.09.2022

Trade name: **COEPLAN 2-K Super sealant glossy transp. (B)**

(Contd. of page 5)

- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Harmful if inhaled.

- LD/LC50 values relevant for classification:

28182-81-2 Hexamethylene diisocyanate, oligomers

Oral	LD50	>5,000 mg/kg (rat) (OECD 423; female)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
		>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	0.402 mg/l (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

822-06-0 hexamethylene-di-isocyanate

Oral	LD50	959 mg/kg (rat) (OECD 401)
Dermal	LD50	>7,000 mg/kg (rat) (OECD 402)
Inhalative	LC50/4 h	0.124 mg/l (rat) (OECD 403)
	ATEmix	1.5 mg/l (rat) (*2)

- Skin corrosion/irritation

Based on available data, the classification criteria are not met.

- Serious eye damage/irritation

Based on available data, the classification criteria are not met.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Germ cell mutagenicity

Based on available data, the classification criteria are not met.

- Carcinogenicity

Based on available data, the classification criteria are not met.

- Reproductive toxicity

Based on available data, the classification criteria are not met.

- STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- STOT-repeated exposure

Based on available data, the classification criteria are not met.

- Aspiration hazard

Based on available data, the classification criteria are not met.

- Additional toxicological information:

* 2 Comment on ATE Information test atmosphere dust / mist:

The test atmosphere generated in the animal study is not representative of the workplace situation, the way the substance is marketed or likely to be used. That's why it can

Test result can not be used directly for hazard assessment. Based on a Expert judgment and weight-of-evidence is a modified classification of the acute Inhalation toxicity justified. Investigation on a comparable product.

Method: Expert assessment of the manufacturer.

- 11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

28182-81-2 Hexamethylene diisocyanate, oligomers

ErC50	>100 mg/l (Scenedesmus subspicatus) (72h; OECD 201)
LC50	>100 mg/l (Danio rerio (Zebraabärbling)) (96h; methods R67/548/EWG AnhangV;C.1)
EC50	645.7 mg/l (Belebtschlamm) (3h; OECD 209)
	>100 mg/l (DESMODESMUS SUBSPICATUS) (72h; OECD 201)
	>100 mg/l (Daphnia magna) (48h; methods R67/548/EWG AnhangV;C.2)

108-65-6 2-methoxy-1-methylethyl acetate

LC50/96 h	>100 mg/l (oryzias latipes (Ricefish))
	161 mg/l (fis)

822-06-0 hexamethylene-di-isocyanate

ErC50	>77.4 mg/l (DESMODESMUS SUBSPICATUS)
LC50/96 h	22 mg/l (Brachydanio rerio (Ricefish))
NOEC	11.7 mg/l (DESMODESMUS SUBSPICATUS) (72 h - EU method C.3)

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.09.2022

Version number 5 (replaces version 4)

Revision: 14.09.2022

Trade name: **COEPLAN 2-K Super sealant glossy transp. (B)**

(Contd. of page 6)

EC0	>89.1 mg/l (daphnia) (48 hour - EU C.2)
EC50	842 mg/l (Bacteria) (3h-static - OECD 209)
LOEC	12.6 mg/l (DESMODESMUS SUBSPICATUS) (72 h - EU method C.3)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations


- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal according to official regulations

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances
17 02 03	plastic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG** Void
- **IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR, IMDG** Void
- **IATA** PAINT
- **14.3 Transport hazard class(es)**
- **ADR, ADN, IMDG**
- **Class** Void
- **IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **14.4 Packing group**
- **ADR, IMDG** Void
- **IATA** III
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Not applicable.
- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

- **Transport/Additional information:**

- **ADR**
- **Remarks:** Kein Gut der Kl. 3 gemäß 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code
ADR IMDG: Verpackung > 450 l = UN 1263 - Kl. 3 - Farbe - VPIII
Außerhalb ADR / IMDG = UN 1263 - Kl. 3 - Farbe - VPIII

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.09.2022

Version number 5 (replaces version 4)

Revision: 14.09.2022

Trade name: **COEPLAN 2-K Super sealant glossy transp. (B)**

(Contd. of page 7)

Not goods of cl. 3 in accordance with 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code
 ADR/IMDG: Packaging > 450 l = UN 1263 - Cl. 3 - Paint - PGIII
 Outside ADR / IMDG = UN 1263 - Cl. 3 - Paint - PGIII

- UN "Model Regulation": Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases**
- | | |
|--------|--|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| EUH204 | Contains isocyanates. May produce an allergic reaction. |

- Department issuing SDS: research & development

- Contact: research & development

- Date of previous version: 31.01.2022

- Version number of previous version: 4

- Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.09.2022

Version number 5 (replaces version 4)

Revision: 14.09.2022

Trade name: **COEPLAN 2-K Super sealant glossy transp. (B)**

(Contd. of page 8)

Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- www.echa.europa.eu
- www.baua.de
IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:
- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp
- www.dguv.de/ifa/gestis/gestis-dnel-liste

- Sources

- * Data compared to the previous version altered.