Safety data sheet

according to 1907/2006/EC, Article 31

S KEMPER

Revision: 28.05.2020

Printing date 28.05.2020 Version number 9 SECTION 1: Identification of the substance/mixture and of the company/undertaking - 1.1 Product identifier **COELAN PRIMER EP PLUS (B)** - Trade name: - 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified use: intended for professional use only! - Application of the substance / the mixture Primer - 1.3 Details of the supplier of the safety data sheet KEMPER SYSTEM GmbH & Co. KG - Manufacturer/Supplier: Holländische Strasse 32-36 34246 Vellmar Deutschland / Germany Telefon: +49 (0)561 / 8295-0 Telefax: +49 (0)561 / 8295-5110 E-Mail: MSDS@KEMPER-SYSTEM.COM research & development - Further information obtainable from: - 1.4 Emergency telephone number: Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen Langenbeckstraße 1; Gebäude 601; 55131 Mainz Tel. Nr.: +49 (0)6131 / 19 24 0 Universitätsmedizin der Johannes Gutenberg-Universität Mainz **SECTION 2: Hazards identification** - 2.1 Classification of the substance or mixture - Classification according to Regulation (EC) No 1272/2008 Acute Tox 4 H302 Harmful if swallowed. Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage. Skin Sens. 1 H317 May cause an allergic skin reaction. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. - 2.2 Label elements - Labelling according to Regulation (EC) No The product is classified and labelled according to the CLP regulation. 1272/2008 - Hazard pictograms GHS05 GHS07 - Signal word Danger - Hazard-determining components of labelling: m-phenylenebis(methylamine) 3-aminomethyl-3,5,5-trimethylcyclohexylamine Phenol, styrenated Polyoxypropylenediamine 3,3,5-trimethylhexamethylene-diamine - Hazard statements H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with - Precautionary statements water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. - 2.3 Other hazards - Results of PBT and vPvB assessment - PBT: Not applicable. - vPvB: Not applicable. (Contd. on page 2)



Printing date 28.05.2020

*

Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Version number 9

Revision: 28.05.2020

(Contd. of page 1)

Trade name: COELAN PRIMER EP PLUS (B)

SECTION 3: Composit	tion/information on ingredients	
- 3.2 Chemical characterisati		
- Description:	Mixture: consisting of the following components.	
- Dangerous components:		
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25-50%
CAS: 61788-44-1 EINECS: 262-975-0 Reg.nr.: 01-2119980970-27	Phenol, styrenated Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1A, H317	25-50%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	12.5-25%
CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 3, H412	12.5-25%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-10%
CAS: 112-53-8 EINECS: 203-982-0 Reg.nr.: 01-2119485976-15	Lauryl alcohol Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Eye Irrit. 2, H319	2.5-10%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17	Salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	2.5-10%
CAS: 2579-20-6 EINECS: 219-941-5 Reg.nr.: 01-2119543741-41	1,3-Cyclohexanedimethanamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Aquatic Chronic 3, H412	2.5-10%
CAS: 13477-34-4 EINECS: 233-332-1 Reg.nr.: 01-2119495093-35	calcium nitrate etrahydrate Eye Dam. 1, H318; Acute Tox. 4, H302	2.5-10%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25	3,3,5-trimethylhexamethylene-diamine Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	2.5-10%
CAS: 38640-62-9 EINECS: 254-052-6 Reg.nr.: 01-2119565150-48	Bis(isopropyl)naphthalene Asp. Tox. 1, H304; Aquatic Chronic 1, H410	0.5-2.5%
- Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

4 1 Description of first aid measures

- 4.1 Description of first aid measures	
- General information:	Immediately remove any clothing soiled by the product.
	Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48
	hours after the accident.
	Do not leave affected persons unattended.
	Personal protection for the First Aider.
	Take affected persons out of danger area and lay down.
- After inhalation:	In case of unconsciousness place patient stably in side position for transportation.
	Supply fresh air; consult doctor in case of complaints.
- After skin contact:	Immediately wash with water and soap and rinse thoroughly.
	Seek medical treatment in case of complaints.
- After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
•	Protect unharmed eye.
- After swallowing:	Drink plenty of water and provide fresh air. Call for a doctor immediately.
Ũ	If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects,	
both acute and delayed	No further relevant information available.
- 4.3 Indication of any immediate medical	
attention and special treatment needed	No further relevant information available.
attention and opeolar reatment needed	



Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.05.2020

Version number 9

Revision: 28.05.2020

Trade name: COELAN PRIMER EP PLUS (B)

(Contd. of page 2)

SECTION 5: Firefighting measure	85
- 5.1 Extinguishing media	CO2 pourder or water enroy. Fight larger firse with water enroy or cleably resistent form
 Suitable extinguishing agents: 	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the	Use me exclusioning methods suitable to surrounding conditions.
substance or mixture	Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters	
- Protective equipment:	Do not inhale explosion gases or combustion gases.
- Additional information	Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
SECTION 6: Accidental release n	neasures
	neasures
- 6.1 Personal precautions, protective	Neasures Wear protective equipment. Keep unprotected persons away.
- 6.1 Personal precautions, protective	Wear protective equipment. Keep unprotected persons away.
- 6.1 Personal precautions, protective	Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Avoid contact with skin and eyes Do not allow product to reach sewage system or any water course.
 - 6.1 Personal precautions, protective equipment and emergency procedures 	Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Avoid contact with skin and eyes Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.
 - 6.1 Personal precautions, protective equipment and emergency procedures 	Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Avoid contact with skin and eyes Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 - 6.1 Personal precautions, protective equipment and emergency procedures - 6.2 Environmental precautions: 	Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Avoid contact with skin and eyes Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. Prevent from spreading (e.g. by damming-in or oil barriers).
 - 6.1 Personal precautions, protective equipment and emergency procedures - 6.2 Environmental precautions: - 6.3 Methods and material for containmental 	Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Avoid contact with skin and eyes Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. Prevent from spreading (e.g. by damming-in or oil barriers).
 - 6.1 Personal precautions, protective equipment and emergency procedures - 6.2 Environmental precautions: 	Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Avoid contact with skin and eyes Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. Prevent from spreading (e.g. by damming-in or oil barriers). nt Do not flush with water or aqueous cleansing agents
 - 6.1 Personal precautions, protective equipment and emergency procedures - 6.2 Environmental precautions: - 6.3 Methods and material for containmental 	Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Avoid contact with skin and eyes Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. Prevent from spreading (e.g. by damming-in or oil barriers).

- 6.4 Reference to other sections

SECTION 7: Handling and storage	
- 7.1 Precautions for safe handling	Ensure good ventilation/exhaustion at the workplace. Store in cool, dry place in tightly closed receptacles. Prevent formation of aerosols.
- 7.2 Conditions for safe storage, including a	ny incompatibilities
- Storage:	
- Requirements to be met by storerooms and	
receptacles:	Store only in the original receptacle.
- Information about storage in one common	
storage facility:	Store away from foodstuffs.
 Further information about storage 	
conditions:	Protect from frost.
	Store in dry conditions.
	Keep container tightly sealed.
	Recommended storage temperature: 5-30 °C
- Storage class:	8 B
- 7.3 Specific end use(s)	No further relevant information available.

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTIO	N 8: Exposure cont	trols/pers	onal protection	
- Additiona technical	l information about des facilities:	ign of	No further data; see item 7.	
	ol parameters ts with limit values that	require mo	nitoring at the workplace:	
- DNELs				
1477-55-0	m-phenylenebis(methy	lamine)		
Inhalative	Acute - systemic effects	1.2 mg/m ³ ((Worker) (GESTIS DNEL List (June 2018))	
	Acute - local effects	0.2 mg/m ³ ((Worker) (GESTIS DNEL List (June 2018))	
- Additiona	l information:	•	The lists valid during the making were used as basis.	
- Personal	ure controls protective equipment: rotective and hygienic r	measures:	The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing	(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.05.2020

Version number 9

Revision: 28.05.2020

Trade name: COELAN PRIMER EP PLUS (B) (Contd. of page 3) Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. - Respiratory protection: When used properly and under normal conditions, breathing protection is not required. Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Respiratory protection - Gas filters and combination filters according to (DIN EN 141) - Protection of hands: Protective gloves Check protective gloves prior to each use for their proper condition. Only use chemical-protective gloves with CE-labelling of category III. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation After use of gloves apply skin-cleaning agents and skin cosmetics. - Material of gloves Recommended materials: Butyl rubber, BR Recommended thickness of the material: $\geq 0.5 \text{ mm}$ Penetration time (min.): < 480 min The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The determined penetration times according to EN 16523-1:2015 are not performed under practical - Penetration time of glove material conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. - As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR Recommended thickness of the material: $\geq 0.1 \text{ mm}$ Penetration time (min.): < 10 - Eye protection: Tightly sealed goggles Protective goggles and facial protection - Classification according to EN 166

- Body protection:

protective clothing (EN 13034)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and cher	mical properties
- General Information	
- Appearance: Form:	Fluid
Colour:	Yellow
- Odour:	Amine-like
- Odour threshold:	Not determined.
- pH-value:	Not determined.
- Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	>200 °C
- Flash point:	>100 °C
- Flammability (solid, gas):	Not applicable.
- Decomposition temperature:	Not determined.
- Auto-ignition temperature:	Product is not selfigniting.
- Explosive properties:	Product does not present an explosion hazard.
- Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
- Density at 20 °C:	1.04 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.
	(Contd on page 5)

(Contd. on page 5)

EN

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.05.2020

Version number 9

Revision: 28.05.2020

Trade name: COELAN PRIMER EP PLUS (B)

		(Contd. of page 4)
- Evaporation rate	Not determined.	
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
- Partition coefficient: n-octanol/water:	Not determined.	
- Viscosity: Dynamic: Kinematic:	Not determined. 700 mPas	
- Solvent content: VOC (EC) - 9.2 Other information	1.28 % No further relevant information available.	

- 10.1 Reactivity	No further relevant information available.
 - 10.2 Chemical stability - Thermal decomposition / conditions to be 	
avoided:	No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions	Violent reactions with: amines and acids.
- 10.4 Conditions to avoid	Store away from heat.
 10.5 Incompatible materials: 	Strong oxidizing agents: amines and acids.
- 10.6 Hazardous decomposition products:	Does not decompose during its intended use.

SECTION 11: Toxicological information

Acute tox		n toxicological effects Harmful if swallowed.	
LD/LC50	values rel	levant for classification:	
1477-55-0) m-pheny	/lenebis(methylamine)	
Oral	LD50	940 mg/kg (rat)	
Inhalative	LC50/4 h	2.4 mg/l (rat)	
61788-44	1 Phenol,	, styrenated	
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
2855-13-2	2 3-aminor	methyl-3,5,5-trimethylcyclohexylamine	
Oral	LD50	1,030 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)	
		propylenediamine	
Oral	LD50	2,885 mg/kg (rat)	
Dermal	LD50	2,980 mg/kg (rabbit)	
	LC50	772 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h, Lit.1 (OECD 203))	
		imethylaminomethyl)phenol	
Oral	LD50	2,169 mg/kg (rat) (OECD 401)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
	LC50	84 mg/l (Scenedesmus subspicatus) (72h; OECD TG 201)	
	Lauryl alco		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)	
	LC50	>100 mg/l (Leuciscus idus (Goldorfe)) (96h; ISO7346)	
	alicylic ac		
Oral	LD50	891 mg/kg (rat)	
		ohexanedimethanamine	
Oral	LD50	793 mg/kg (rat)	
Dermal	LD50	1,100 mg/kg (ATE)	
		n nitrate etrahydrate	
Oral	LD50	500 mg/kg (ATE)	
Dermal	LD50	300-2,000 mg/kg (rat) (OECD 423)	



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.05.2020

Version number 9

Revision: 28.05.2020

Trade name: COELAN PRIMER EP PLUS (B)

		(Contd. of page 5)
25513-64-8 3,3,5-trimethylhexamethylene-d	iamine	
Oral LD50 500 mg/kg (ATE)		
- Primary irritant effect:		
- Skin corrosion/irritation	Causes severe skin burns and eye damage.	
 Serious eye damage/irritation 	Causes serious eye damage.	
 Respiratory or skin sensitisation 	May cause an allergic skin reaction.	
 CMR effects (carcinogenity, mutagenicity a 	nd toxicity for reproduction)	
 Germ cell mutagenicity 	Based on available data, the classification criteria are not met.	
- Carcinogenicity	Based on available data, the classification criteria are not met.	
 Reproductive toxicity 	Based on available data, the classification criteria are not met.	
 STOT-single exposure 	Based on available data, the classification criteria are not met.	
 STOT-repeated exposure 	Based on available data, the classification criteria are not met.	
- Aspiration hazard	Based on available data, the classification criteria are not met.	

SECTIO	N 12: Ecological information	on	
- 12.1 Toxic			
- Aquatic to	2		
	m-phenylenebis(methylamine)		
	87.6 mg/l (oryzias latipes (Ricefisl		
EC50	15.2 mg/l (daphnia) (48h)	'')	
	1 Phenol, styrenated		
LL 50	14.8 mg/l (fish) (96h)		
EL50	3.14 mg/l (Scenedesmus subspice	atus) (72h)	
LLOO	1-10 mg/l (Daphnia magna) (48h)		
2855-13-2	3-aminomethyl-3,5,5-trimethylcy	clohexylamine	
	110 mg/l (Brachydanio rerio (Rice		
EC50	23 mg/l (daphnia)		
2000	15.2 mg/l (Daphnia magna)		
EC50	37 mg/l (Scenedesmus subspicate	us)	
LC 50	87.6 mg/l (oryzias latipes (Ricefisl		
	Polyoxypropylenediamine		
EC50	80 mg/l (Daphnia magna) (48h; O	ECD 202 static)	
EC50	15 mg/l (Pseudokirchneriella subo		
	4,6-tris(dimethylaminomethyl)pho		
	175 mg/l (Cyprinus Carpio) (96h)		
EC50	750 mg/l (daphnia) (96h)		
EC50	222 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (24h)		
	Lauryl alcohol		
EC50	>0.01-1 mg/l (Selenastrum caprice	ornutum) (OFCD 201)	
EC0	>100 mg/l (Pseudomonas putida)		
NOEC	>0.001-0.01 mg/l (Daphnia magna		
	1,3-Cyclohexanedimethanamine		
EC50	58.4 mg/l (ALGAE) (72h)		
EC50	130 mg/l (Leuciscus idus) (96h; g	olden orfe)	
EC50	33.1 mg/l (Daphnia magna) (48h;		
	8 3,3,5-trimethylhexamethylene-d		
EC50	29.5 mg/l (Scenedesmus subspice		
LC50	174 mg/l (Leuciscus idus melanot		
	istence and degradability	No further relevant information available.	
	ccumulative potential	No further relevant information available.	
- 12.4 Mobi	lity in soil	No further relevant information available.	
- Ecotoxica	al effects:		
- Remark:	l ecological information:	Toxic for fish	
- Additiona - General n		Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water	
		Do not allow product to reach ground water, water course or sewage system.	
		Must not reach sewage water or drainage ditch undiluted or unneutralised.	
		Danger to drinking water if even small quantities leak into the ground.	
			(Contd on page 7

(Contd. on page 7) - EN



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 9

Printing date 28.05.2020

Revision: 28.05.2020

(Contd. of page 6)

EN

Trade name: COELAN PRIMER EP PLUS (B)

 Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

 - 12.5 Results of PBT and vPvB assessment

 - PBT:
 Not applicable.

 - vPvB:
 Not applicable.

 - 12.6 Other adverse effects
 No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods - Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal according to official regulations

- European waste catalogue	
08 04 09* waste a	adhesives and sealants containing organic solvents or other hazardous substances
08 04 10 waste a	adhesives and sealants other than those mentioned in 08 04 09

- Uncleaned packaging: - Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name ADR	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)
IMDG	CALCIUM NITRATE), ENVIRONMENTALLY HAZARDOUS AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), CALCIUM NITRATE), MARINE POLLUTANT
ΙΑΤΑ	AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), CALCIUM NITRATE)
14.3 Transport hazard class(es)	
ADR	
Class Label	8 (C7) Corrosive substances.
Class Label	8 Corrosive substances. 8
IATA	
Class Label	8 Corrosive substances. 8
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant: Special marking (ADR):	Product contains environmentally hazardous substances: Phenol, styrenated Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Corrosive substances.

Page 7/9



Page 8/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.05.2020

Version number 9

Revision: 28.05.2020

Trade name: COELAN PRIMER EP PLUS (B)

	(Contd. of page 7
- Hazard identification number (Kemler code):	80
- EMS Number:	F-A,S-B
- Segregation groups	Alkalis
- Stowage Category	A
- Segregation Code	SG35 Stow "separated from" SGG1-acids
- 14.7 Transport in bulk according to Annex II of Marpol a	nd the IBC
Code	Not applicable.
- Transport/Additional information:	
- ADR	
 Limited quantities (LQ) 	1L
 Excepted quantities (EQ) 	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
- Transport category	2
- Tunnel restriction code	Ε
- IMDG	
- Limited quantities (LQ)	1L
 Excepted quantities (EQ) 	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (M- PHENYLENEBIS(METHYLAMINE), CALCIUM NITRATE), 8, 11,
	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information - 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture - Directive 2012/18/EU - Named dangerous substances - ANNEX I None of the ingredients is listed. E2 Hazardous to the Aquatic Environment - Seveso category - Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t - Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3 - National regulations: - Information about limitation of use: Employment restrictions concerning juveniles must be observed. Employment restrictions concerning women of child-bearing age must be observed. Employment restrictions concerning pregnant and lactating women must be observed.

- 15.2 Chemical safety assessment:

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2015/830 - Relevant phrases H302 Harmful if swallowed

A Chemical Safety Assessment has not been carried out.

noiorant pinacee	
-	H304 May be fatal if swallowed and enters airways.
	H312 Harmful in contact with skin.
	H314 Causes severe skin burns and eye damage.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H318 Causes serious eye damage.
	H319 Causes serious eye irritation.
	H332 Harmful if inhaled.
	H361d Suspected of damaging the unborn child.
	H400 Very toxic to aquatic life.
	H410 Very toxic to aquatic life with long lasting effects.
	H411 Toxic to aquatic life with long lasting effects.
	H412 Harmful to aquatic life with long lasting effects.
- Department issuing SDS:	research & development
- Contact:	research & development

(Contd. on page 9)



Page 9/9

EN

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.05.2020

Version number 9

Revision: 28.05.2020

Trade name: COELAN PRIMER EP PLUS (B)

	(Contd. of page 8)
- Abbreviations and acronyms:	(Contd. of page 8) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal concentration, 50 percent DD51: Lethal concentration, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral - Category 4 Skin Corr. 18: Skin corrosion/irritation - Category 1A Skin Corr. 10: Skin corrosion/irritation - Category 1 Skin Irrit. 2: Skin corrosion/irritation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Aguatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
	Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Sources	Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 - www.echa.europa.eu
bources	- www.baua.de
	- www.bada.ue IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance: - www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp - www.dguv.de/ifa/gestis/gestis-dnel-liste
 * Data compared to the previous version altered. 	