

according to 1907/2006/EC, Article 31

Printing date 12.01.2017 Version number 2 Revision: 12.01.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

COEPLAN 2-K Poured coating coloured (A) - Trade name:

- 1.2 Relevant identified uses of the substance or mixture and uses advised

Identified use: intended for professional use only!

- Application of the substance / the mixture Coating - 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: KEMPER SYSTEM GmbH & Co. KG

Holländische Strasse 32-36 34246 Vellmar Deutschland / Germany

Telefon: +49 (0)561 / 8295-0 Telefax: +49 (0)561 / 8295-5110 E-Mail: MSDS@KEMPER-SYSTEM.COM

- Further information obtainable from: Research and Development

- 1.4 Emergency telephone number: Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen

Langenbeckstraße 1; Gebäude 601; 55131 Mainz

Tel. Nr.: +49 (0)6131 / 19 24 0

Universitätsmedizin der Johannes Gutenberg-Universität Mainz

#### **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC)

No 1272/2008 The product is not classified according to the CLP regulation.

- 2.2 Label elements

- Labelling according to Regulation (EC) No

1272/2008 Void - Hazard pictograms Void Signal word Void - Hazard statements

- 2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable. - vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- 3.2 Chemical characterisation: Mixtures

- Description: Mixture of substances listed below with nonhazardous additions

- Dangerous components:						
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural	substance with a Community workplace exposure limit	25-50%			
CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light	Flam. Liq. 3, H226; Asp. Tox. 1, H304	2.5-10%			
CAS: 71302-91-5 EC number: 615-277-9	Hydrocarbons, C9-unsatd., polymers with phenol	Acute Tox. 4, H302	0.5-2.5%			
CAS: 108-83-8 EINECS: 203-620-1	2,6-dimethylheptan-4-one	Flam. Liq. 3, H226; STOT SE 3, H335	0.5-2.5%			
- Additional information: For the wording of the listed hazard phrases refer to section 16						

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

4.1 Description of first aid measures

 General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Do not leave affected persons unattended. Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eve.

- After swallowing: 4.2 Most important symptoms and effects,

both acute and delayed

- After inhalation:

- After skin contact:

No further relevant information available.

If symptoms persist consult doctor.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 12.01.2017 Version number 2 Revision: 12.01.2017

Trade name: COEPLAN 2-K Poured coating coloured (A)

 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. of page 1)

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media

- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture

- 5.3 Advice for firefighters

No further relevant information available.

Protective equipment:
 Additional information

Do not inhale explosion gases or combustion gases.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

# **SECTION 6: Accidental release measures**

 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

- 6.2 Environmental precautions:

- 6.4 Reference to other sections

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water. Prevent from spreading (e.g. by damming-in or oil barriers).

- 6.3 Methods and material for containment

and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents See Section 7 for information on safe handling.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles. Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

Information about fire - and explosion

protection:

No special measures required.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

Requirements to be met by storerooms and

receptacles:

Store only in the original receptacle.

- Information about storage in one common

storage facility:

Store away from foodstuffs.

- Further information about storage

conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

Recommended storage temperature: 10-30 ℃

- Storage class:

- 7.3 Specific end use(s)

No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

- Additional information about design of

technical facilities:

No further data; see item 7.

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

WEL Long-term value: 10\* 4\*\* mg/m³ \*inhalable dust \*\*respirable dust

108-83-8 2,6-dimethylheptan-4-one

WEL Long-term value: 148 mg/m³, 25 ppm

Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 3)

(Contd. of page 2)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.01.2017 Version number 2 Revision: 12.01.2017

Trade name: COEPLAN 2-K Poured coating coloured (A)

- Respiratory protection: When used properly and under normal conditions, breathing protection is not required.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- Protection of hands:



Protective gloves

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the

preparation.

Check protective gloves prior to each use for their proper condition.

Selection of the glove material on consideration of the penetration times, rates of diffusion

and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is

recommended.

- As protection from splashes gloves made of

the following materials are suitable:

- Penetration time of glove material

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.1 \text{ mm}$ 

Penetration time (min.): <10

Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing Impervious protective clothing

#### **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Fluid

Colour: According to product specification
Odour: Characteristic

- Odour threshold: Not determined.
- pH-value: Not determined.

- Change in condition

Melting point/freezing point:
Initial boiling point and boiling range:

- Flash point:

Not applicable.

- Flammability (solid, gas):

- Ignition temperature:

Decomposition temperature: Not determined.

- Auto-ignition temperature: Product is not selfigniting

- Explosive properties: Product does not present an explosion hazard.

Not applicable.

Not determined.

- Explosion limits:

- Evaporation rate

Lower:
Upper:

Density at 20 °C:
Relative density
Vapour density

Not determined.

1.45 g/cm³
Not determined.
Not determined.

- Solubility in / Miscibility with

water: Not miscible or difficult to mix.

- Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 12.01.2017 Version number 2 Revision: 12.01.2017

Trade name: COEPLAN 2-K Poured coating coloured (A)

(Contd. of page 3)

- Viscosity:

**Dynamic:** Not determined. Kinematic: Not determined

- Solvent content:

VOC (EC) 2.50 %

9.2 Other information No further relevant information available

# **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be

avoided:

- 10.3 Possibility of hazardous reactions - 10.4 Conditions to avoid

 10.5 Incompatible materials: - 10.6 Hazardous decomposition products:

No decomposition if used according to specifications.

No dangerous reactions known.

No further relevant information available. No further relevant information available. No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:
---

7727-43-7 barium sulphate, natural

LD50 >15000 mg/kg (rat)

Dermal LD50 > 2000 mg/kg (rat)

#### 64742-47-8 Distillates (petroleum), hydrotreated light

LD50 > 5000 mg/kg (rat) Dermal LD50 > 2000 mg/kg (rab)

#### 71302-91-5 Hydrocarbons, C9-unsatd., polymers with phenol

Oral LD50 1200-2000 mg/kg (rat)

## 108-83-8 2,6-dimethylheptan-4-one

LD50 | 5750 mg/kg (rat) Oral Dermal LD50 16000 mg/kg (rabbit)

Primary irritant effect:

 Skin corrosion/irritation Based on available data, the classification criteria are not met. - Serious eye damage/irritation Based on available data, the classification criteria are not met. - Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) - Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. - STOT-single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. STOT-repeated exposure - Aspiration hazard Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

- 12.1 Toxicity

Aquatic toxicity:

7727-43-7 barium sulphate, natural

EC50 32 mg/l (Daphnia magna) (Ba-lon; 48 h)

12.2 Persistence and degradability No further relevant information available. - 12.3 Bioaccumulative potential No further relevant information available. - 12.4 Mobility in soil No further relevant information available.

- Additional ecological information:

- General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

system.

- 12.5 Results of PBT and vPvB assessment

Not applicable. - PRT-- vPvB: Not applicable.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 12.01.2017 Version number 2 Revision: 12.01.2017

Trade name: COEPLAN 2-K Poured coating coloured (A)

- 12.6 Other adverse effects No further relevant information available (Contd. of page 4)

## **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Void

European waste catalogue

08 04 09\* | waste adhesives and sealants containing organic solvents or other hazardous substances

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

# **SECTION 14: Transport information**

4.4	4	LINI	Mirror	shor

- ADR, ADN, IMDG, IATA
- 14.2 UN proper shipping name
- ADR, ADN, IMDG, IATA Void
- 14.3 Transport hazard class(es)
- ADR, ADN, IMDG, IATA
- Class
- 14.4 Packing group
- ADR, IMDG, IATA Void
- 14.5 Environmental hazards:
- Marine pollutant: No
- 14.6 Special precautions for user Not applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC

Code Not applicable.

- UN "Model Regulation": Void

#### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

- Department issuing SDS:

Sources

research & development research & development

Contact:

- Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

Internet:

- www.echa.com - www.baua.de

(Contd. on page 6)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2017 Version number 2 Revision: 12.01.2017

Trade name: COEPLAN 2-K Poured coating coloured (A)

(Contd. of page 5)

- www.gestis.itrust.de (IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance)

- \* Data compared to the previous version