

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **COETRANS 1-K Waterproofing Layer**
- **UFI:** JEK8-QQHV-300D-E9AP
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the mixture** Identified use: intended for professional use only!
Waterproofing
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** KEMPER SYSTEM LTD
Kemper House
30 Kingsland Grange
Warrington
WA1 4RW
www.kempersystem.co.uk
enquiries@kempersystem.co.uk
phone: +44 (0)1925 445532
fax: +44 (0)1925 575096
- **Further information obtainable from:** research & development
- **1.4 Emergency telephone number:** Medical Emergency information in case of poisoning:
Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240
(advisory service in German or English language)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- Flam. Liq. 3 H226 Flammable liquid and vapour.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2 H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements

- **Labelling according to Regulation (EC) No 1272/2008**
- **Hazard pictograms**

The product is classified and labelled according to the GB CLP regulation.



GHS02 GHS07 GHS08

- **Signal word**
- **Hazard-determining components of labelling:**

Warning

Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene
Reaktionsmasse von Ethylbenzol und Xylol
Urethane bis Oxazolidine
Isophorondiisocyanate homopolymer
Phenol, methylstyrenated
hexahydromethylphthalic anhydride
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
m-tolylidene diisocyanate

- Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: COETRANS 1-K Waterproofing Layer

(Contd. of page 1)

- **Additional information:** EUH204 Contains isocyanates. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
As from 24 August 2023 adequate training is required before industrial or professional use.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

- Determination of endocrine-disrupting properties

68512-30-1 | Phenol, methylstyrenated

List II

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture: consisting of the following components.

- Dangerous components:

CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35	barium sulphate, natural substance with a Community workplace exposure limit	25-50%
EC number: 905-588-0 Reg.nr.: 01-2119486136-34	Reaktionsmasse von Ethylbenzol und Xylol Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-12.5%
CAS: 37273-56-6 EC number: 609-378-7	Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene Eye Irrit. 2, H319; Skin Sens. 1, H317	10-12.5%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	2.5-10%
CAS: 59719-67-4 EINECS: 261-879-6 Reg.nr.: 01-2119983487-19	Urethane bis Oxazolidine Aquatic Chronic 2, H411; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥2.5-<10%
CAS: 53880-05-0 EC number: 931-312-3 Reg.nr.: 01-2119488734-24	Isophorondiisocyanate homopolymer Skin Sens. 1, H317; STOT SE 3, H335	≥1-<2.5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide Carc. 2, H351	0.5-2.5%
CAS: 68512-30-1 EINECS: 270-966-8 Reg.nr.: 01-2119555274-38	Phenol, methylstyrenated Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	0.5-2.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	hydrocarbons, C9, aromatic Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	≥0.5-<2.5%
CAS: 25550-51-0 EINECS: 247-094-1 Index number: 607-241-00-6 Reg.nr.: 01-2119845474-33	hexahydromethylphthalic anhydride Resp. Sens. 1, H334; Eye Dam. 1, H318; Skin Sens. 1, H317	≥0.1-<0.5%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5 Reg.nr.: 01-2119490408-31	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.25%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34	m-tolyldiene diisocyanate Acute Tox. 2, H330; Resp. Sens. 1, H334; Carc. 2, H351; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	<0.1%

- SVHC

25550-51-0 | hexahydromethylphthalic anhydride

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: **COETRANS 1-K Waterproofing Layer**

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Do not leave affected persons unattended.
Personal protection for the First Aider.
Take affected persons out of danger area and lay down.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment in case of complaints.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Protect unharmed eye.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.
Nitrogen oxides (NO_x)
Carbon monoxide (CO)
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
Avoid contact with skin and eyes
Keep away from ignition sources.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
Prevent from spreading (e.g. by damming-in or oil barriers).
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: **COETRANS 1-K Waterproofing Layer**

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Store in dry conditions.
Protect from frost.
Keep container tightly sealed.
Recommended storage temperature: 5-30 °C
- **Storage class:** 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
-----	---

Reaktionsmasse von Ethylbenzol und Xylol

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk, BMGV
-----	--

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

26471-62-5 m-tolidene diisocyanate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

- **Regulatory information** WEL: EH40/2020

- DNELs

7727-43-7 barium sulphate, natural

Inhalative	Acute - systemic effects	10 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))
------------	--------------------------	--

Reaktionsmasse von Ethylbenzol und Xylol

Inhalative	Acute - systemic effects	221 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))
	Long term - systemic effects	221 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))

- Ingredients with biological limit values:

Reaktionsmasse von Ethylbenzol und Xylol

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

BMGV	1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine
------	--

- **Additional information:** The lists valid during the making were used as basis.

- 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:** The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: **COETRANS 1-K Waterproofing Layer**

(Contd. of page 4)

- Respiratory protection:

Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
When used properly and under normal conditions, breathing protection is not required.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2

- Hand protection

Respiratory protection - Gas filters and combination filters according to (DIN EN 141)



Protective gloves

Check protective gloves prior to each use for their proper condition.
Only use chemical-protective gloves with CE-labelling of category III.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves

Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time (min.): < 480

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.1 mm

Penetration time (min.): < 10

- Eye/face protection



Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166

- Body protection:

Protective work clothing
protective clothing (EN 13034)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Colour:	According to product specification
- Odour:	Characteristic
- Odour threshold:	Not determined.
- Melting point/freezing point:	Undetermined.
- Boiling point or initial boiling point and boiling range	36 °C
- Flammability	Not applicable.
- Lower and upper explosion limit	
- Lower:	Not determined.
- Upper:	Not determined.
- Flash point:	25 °C (DIN EN 22719)
- Decomposition temperature:	Not determined.
- pH	Not determined.
- Viscosity:	
- Kinematic viscosity at 20 °C	110 s (ISO 6 mm)
- Dynamic:	Not determined.
- Solubility	
- water:	Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value)	Not determined.
- Density and/or relative density	
- Density at 20 °C:	1.56 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: **COETRANS 1-K Waterproofing Layer**

(Contd. of page 5)

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Solvent separation test:**
- **VOC (EC)** 10.70 %
- **Change in condition**
- **Evaporation rate** Not determined.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Flammable liquid and vapour.
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with humid air.
- **10.4 Conditions to avoid** Keep away from open flames/heat sources.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: COETRANS 1-K Waterproofing Layer

(Contd. of page 6)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

7727-43-7 barium sulphate, natural

Oral	LD50	>15,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

Reaktionsmasse von Ethylbenzol und Xylol

Oral	LD50	5,251 mg/kg (mouse) 4,300 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.7 mg/l (rat)

37273-56-6 Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)

59719-67-4 Urethane bis Oxazolidine

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rab)

53880-05-0 Isophorondiisocyanate homopolymer

Oral	LD50	>14,000 mg/kg (rat) (OECD 401)
------	------	--------------------------------

68512-30-1 Phenol, methylstyrenated

Oral	LD50	>2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	14,112 mg/kg (rat)
Inhalative	LC50/4 h	23.4 mg/l (rat) (OECD Guideline 403 (Acute Inhalation Toxicity))

hydrocarbons, C9, aromatic

Oral	LD50	>3,492 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)

25550-51-0 hexahydromethylphthalic anhydride

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Inhalative	LC50/4 h	0.05 mg/l (ATE)
------------	----------	-----------------

26471-62-5 m-tolylidene diisocyanate

Oral	LD50	5,110 mg/kg (rat)
Inhalative	LC50/4 h	0.107 mg/l (rat)
	LC50/1 h	0.47 mg/l (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

- 11.2 Information on other hazards

- Endocrine disrupting properties

68512-30-1	Phenol, methylstyrenated	
------------	--------------------------	--

List II

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: **COETRANS 1-K Waterproofing Layer**

(Contd. of page 7)

128-37-0 | 2,6-di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

7727-43-7 barium sulphate, natural

EC50 32 mg/l (Daphnia magna) (Ba-Ion; 48 h)

Reaktionsmasse von Ethylbenzol und Xylol

LC50/96 h 26.7 mg/l (Pimephales promelas)
 LC50 2.6 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h; OECD 203)
 EC50 2.2 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
 IC50 2.2 mg/l (ALGAE)
 NOEC 157 mg/l (Belebschlamm) (OECD 209)
 1.17 mg/l (Ceriodaphnia dubia) (7d; US EPA 600/4-91/003)
 >1.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (56d)
 IC50 1 mg/l (Daphnia magna) (24h; OECD 202)

37273-56-6 Poly[oxy(methyl-1,2-ethanediyl)], alpha-hydro-omega-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene

EC50 >10,000 mg/l (Belebschlamm) (OECD 209)

64742-95-6 Solvent naphtha (petroleum), light arom.

LL 50 9.2 mg/l (fish) (96h; OECD 203)
 EC50 3.2 mg/l (Daphnia magna) (48h; OECD 202)
 EC50 2.6 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)

59719-67-4 Urethane bis Oxazolidine

EC50 87.1 mg/l (Daphnia magna) (48h)
 EC50 18.6 mg/l (Senastrum capricornutum) (72h)

53880-05-0 Isophorondiisocyanate homopolymer

LC50/96 h >1.51 mg/l (Cyprinus Carpio) (Richtlinie 67/548/EWG, Anhang V, C.1.)
 EC50 >3.36 mg/l (Daphnia magna) (OECD 202)
 EC50 >10,000 mg/l (Belebschlamm) (OECD 209)

68512-30-1 Phenol, methylstyrenated

ErC50 15 mg/l (daphnia) (OECD TG 201)
 LC50/96 h 25.8 mg/l (daphnia) (OECD TG 203)
 EC50 14-51 mg/l (daphnia) (OECD TG 202)

123-86-4 n-butyl acetate

LC50/96 h 18 mg/l (PISCIS - Fisch) (OECD 203 (96 hr))
 NOEC 200 mg/l (DESMODESMUS SUBSPICATUS)
 EC50 44 mg/l (daphnia) (OECD 202 (48 hr))
 EC50 >100 mg/l (ALGAE)
 647.7 mg/l (DESMODESMUS SUBSPICATUS)
 EC50 72.8 mg/l (daphnia)
 IC50 356 mg/l (Tetrahymena)

hydrocarbons, C9, aromatic

LL 50 9.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96h; OECD 203)
 EL50 2.9 mg/l (Pseudokirchneriella subcapitata) (72h; OECD 201)
 3.2 mg/l (Daphnia magna) (48h; OECD 202)
 EC50 >99 mg/l (Belebschlamm) (10 min.; OECD 209)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- Remark: Harmful to fish

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: **COETRANS 1-K Waterproofing Layer**

(Contd. of page 8)

- Additional ecological information:

- General notes:

Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal according to official regulations

- European waste catalogue

08 05 01*	waste isocyanates
15 01 10*	packaging containing residues of or contaminated by hazardous substances
17 02 03	plastic

- Uncleaned packaging:

- Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN number or ID number

- ADR, IMDG

- IATA

Void
UN1263

- 14.2 UN proper shipping name

- ADR, IMDG

- IATA

Void
PAINT

- 14.3 Transport hazard class(es)

- ADR, ADN, IMDG

- Class

Void

- IATA



- Class

- Label

3 Flammable liquids.
3

- 14.4 Packing group

- ADR, IMDG

- IATA

Void
III

- 14.5 Environmental hazards:

- Marine pollutant:

No

- 14.6 Special precautions for user

Not applicable.

- 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

- Transport/Additional information:

- ADR

- Remarks:

Kein Gut der Kl. 3 gemäß 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code
ADR IMDG: Verpackung > 450 l = UN 1263 - Kl. 3 - Farbe - VPIII
Außerhalb ADR / IMDG = UN 1263 - Kl. 3 - Farbe - VPIII

Not goods of cl. 3 in accordance with 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code
ADR/IMDG: Packaging > 450 l = UN 1263 - Cl. 3 - Paint - PGIII
Outside ADR / IMDG = UN 1263 - Cl. 3 - Paint - PGIII

- UN "Model Regulation":

Void

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: **COETRANS 1-K Waterproofing Layer**

(Contd. of page 9)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category** P5c FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 74

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- National regulations:

- Substances of very high concern (SVHC) according to UK REACH

25550-51-0 | hexahydromethylphthalic anhydride

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH204 Contains isocyanates. May produce an allergic reaction.

- **Department issuing SDS:** research & development

- **Contact:** research & development

- **Date of previous version:** 13.06.2022

- **Version number of previous version:** 11

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2022

Version number 12 (replaces version 11)

Revision: 26.08.2022

Trade name: COETRANS 1-K Waterproofing Layer

(Contd. of page 10)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 2: Acute toxicity – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- www.echa.europa.eu
- www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:
- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp
- www.dguv.de/ifa/gestis/gestis-dnel-liste

- Sources

- * Data compared to the previous version altered.